

--upwardly--

a continuous curved surface extending from said upper edge of said first planar surface to said front edge of said second planar surface;

said curved surface having a convex configuration adjacent said upper edge adapted to support the legs of a user in a generally upright position and a concave configuration extending continuously with said convex configuration ending at said front edge and tapering to form a thin lower portion of said pillow to simultaneously maintain the buttocks of a user in an elevated position.

15. A device for enabling a female user to comfortably retain after sexual intercourse a position that will enhance the likelihood of becoming pregnant comprising:

a continuously extending curved surface including a concave lower section for placement beneath the buttocks of a user to maintain the hips of said user in an elevated position; and a convex upper section extending continuously upwardly from said lower section for at least 16 inches and cooperating therewith to support the legs of said user in a generally upright position.

16. A postcoital positioning device for maintaining a female user after sexual intercourse in a position for achieving conception having a continuously extending curved surface comprising:

a concave lower portion to be placed beneath the buttocks of a user to maintain the hips of said user in a raised position; and

a convex portion extending from said lower portion to maintain the legs of said user in a generally upright position while said buttocks are supported upon said lower concave portion;

said concave portion terminating in a thin lower portion for facilitating placement thereof beneath said buttocks.

17. A device for postcoital positioning of female user comprising:

a continuously extending curved surface, said curved surface being formed with a concave lower portion for placement beneath the buttocks of a user to support said buttocks and having a width sufficient to maintain the hips of said user in an elevated position, and a convex upper portion contiguous with said lower portion and extending upwardly there from when said device is in use a distance sufficient to maintain the legs of said user in an upwardly directed position while said buttocks are supported upon said lower portion.

18. A device for postcoital positioning of a female user comprising a continuously extending curved surface having concave lower means with a wedge shaped thinning configuration for elevating the buttocks of said user and convex upper means cooperating with said concave lower means for simultaneously supporting the legs of said user in a generally upright position.

² 19. A device according to Claims 1, ~~2, 3, 4, or 5~~ comprising a base member made of foam rubber.

³ 20. A device according to Claim ~~19~~² comprising a removable cover extending about said foam rubber base member and enclosing said base member therein.

⁴ 21. A device according to Claims ~~14, 15, 16, 17, or 18~~¹ comprising a width of between 14 and 18 inches and a height of between 16 and 20 inches.

⁵ 22. A device according to Claim ~~14~~¹ wherein said first planar surface and said second planar surface have a width of between 14 and 18 inches; wherein said first planar surface has a height of between 16 and 20 inches; wherein said second planar surface has a depth of between 18 and 25 inches; said device further comprising a thickness extending between said first planar surface and said curved surface of between 8 and 12 inches.

⁶ 23. A device according to Claims ~~14, 15, 16, 17, 18, 20, or 22~~^{1 3 5} comprising a pair of handles located on opposite sides thereof to facilitate use of said device.

⁷ 24. A device according to Claim ~~14~~¹ wherein said concave configuration tapers toward said front edge to meet said second planar surface to form therewith said very thin lower portion.

⁸ 25. A device according to Claim ~~19~~² comprising a pair of handles located on opposite sides thereof to facilitate use of said device.

Art Unit: ***

CLMPTO

WAB

2/26/05

Claims 1 thru 13 were cancelled.

14. A device for postcoital positioning of a female user comprising:

a first planar surface extending vertically while said device is in use,

said first planar surface having an upper and a lower edge;

a second planar surface extending horizontally when said device is in use and extending perpendicularly relative to said first planar surface, said second planar surface having a front and a rear edge;

with said lower edge of said first planar surface extending contiguously with said rear edge of said second planar surface; and

a continuous curved surface extending from said upper edge of said first planar surface to said front edge of said second planar surface;

said curved surface having a convex configuration adjacent said upper edge adapted to support the legs of a user in a generally upright position and a concave configuration extending continuously with said convex configuration ending at said front edge and tapering to form a thin lower portion of said pillow to simultaneously maintain the buttocks of a user in an elevated position.

Claims 15 thru 18 were cancelled.

Art Unit: ***

19. A device according to Claims 1, 2, 3, 4, or 5 comprising a base member made of foam rubber.

20. A device according to Claim 19 comprising a removable cover extending about said foam rubber base member and enclosing said base member therein.

21. A device according to Claims 14, 15, 16, 17, or 18 comprising a width of between 14 and 18 inches and a height of between 16 and 20 inches.

22. A device according to Claim 14 wherein said first planar surface and said second planar surface have a width of between 14 and 18 inches; wherein said first planar surface has a height of between 16 and 20 inches; wherein said second planar surface has a depth of between 18 and 25 inches; said device further comprising a thickness extending between said first planar surface and said curved surface of between 8 and 12 inches.

23. A device according to Claims 14, 15, 16, 17, 18, 20, or 22 comprising a pair of handles located on opposite sides thereof to facilitate use of said device.

24. A device according to Claim 14 wherein said concave configuration tapers toward said front edge to meet said second planar surface to form therewith said very thin lower portion.

25. A device according to Claim 19 comprising a pair of handles located on opposite sides thereof to facilitate use of said device.

26. A device according to Claim 21 comprising a pair of handles located on opposite sides thereof to facilitate use of said device.